Towel Warmer - Technical Specification

Primaflow F&P

425330BK

| | EAN | 5060235349911 | |
|-------------------------------------|--|----------------------|--|
| 1 | Finish | Straight Black | |
| Linit | Width | 500mm | |
| | Height | 750mm | |
| | Fitted Depth | 79mm | |
| | Horizontal Profile Size | 22mm | |
| | Vertical Profile Size | 40mm x 30mm D Shaped | |
| | Thread to Thread Centre | 455mm | |
| | Wall to Thread Centre | 64mm | |
| | Thread Orientation | Vertical Into Bottom | |
| | Thread Size | 1/2" BSP | |
| 0 | Weight | 5.3 kg | |
| Installation & Usage Options | | | |
| Central Heating System | | | |
| ł | Thermal Output dt50 | 317 Watts – 1081 BTU | |
| | Thermal Output dt30 | 174 Watts – 593 BTU | |
| | Maximum Working Pressure | 1000 kPa – 10 Bar | |
| Option – Electric Only or Dual Fuel | | | |
| A | 250 Watts Electrical Element Kit – EAN 5060235341502 | | |

Fitted Dimensions

| Product Information | | | |
|---|--|--|--|
| Conform to EN 442 standard | | | |
| CE Mark applied | | | |
| Brackets and Fixings included Specification | | | |
| Pressure tightness: No leakage at 1.3 x MOP | | | |
| Resistance to pressure: No breakage at 1.5 x MOP | | | |
| Maximum operating pressure (MOP): 1000 kPa | | | |
| Maximum surface temperature: 110°C | | | |
| Resistance against corrosion: No corrosion after 100 h humidity | | | |