

Compress 2000 AWF

CS2000AWF 10 R-S

7738602280

To the extent applicable to the product, the following data are based on the requirements of Regulations (EU) 811/2013 and (EU) 813/2013.

Productdata	Symbol	Unit	7738602280
Energy Efficiency Class			A++
Energy efficiency class (low temperature application)			A+++
Rated heat output (average climate conditions)	Prated	kW	8
Rated heat output (low temperature application, average climate conditions)	Prated	kW	9
Seasonal space heating energy efficiency (average climate conditions)	η_s	%	136
Seasonal space heating energy efficiency (low temperature application, average climate conditions)	η_s	%	205
Annual energy consumption (average climate conditions)	Q_{HE}	kWh	4567
Annual energy consumption (low temperature application, average climate conditions)	Q_{HE}	kWh	3644
Sound power level, indoors	L_{WA}	dB	-
Special precautions to be taken during assembly, installation or maintenance (if applicable): see product accompanying documents			
Rated heat output (colder climate conditions)	Prated	kW	7
Rated heat output (low temperature application, colder climate conditions)	Prated	kW	8
Rated heat output (warmer climate conditions)	Prated	kW	9
Rated heat output (low temperature application, warmer climate conditions)	Prated	kW	9
Seasonal space heating energy efficiency (colder climate conditions)	η_s	%	117
Seasonal space heating energy efficiency (low temperature application, colder climate conditions)	η_s	%	170
Seasonal space heating energy efficiency (warmer climate conditions)	η_s	%	182
Seasonal space heating energy efficiency (low temperature application, warmer climate conditions)	η_s	%	281
Annual energy consumption (colder climate conditions)	Q_{HE}	kWh	5539
Annual energy consumption (low temperature application, colder climate conditions)	Q_{HE}	kWh	4423
Annual energy consumption (warmer climate conditions)	Q_{HE}	kWh	2496
Annual energy consumption (low temperature application, warmer climate conditions)	Q_{HE}	kWh	1617
Sound power level, outdoors	L_{WA}	dB	60
Air-to-water heat pump			Yes
Water-to-water heat pump			No
Brine-to-water heat pump			No
Low temperature heat pump			No
Equipped with a supplementary heater?			Yes
Heat pump combination heater			No
Additional data for integrated temperature control			
Class of the temperature control			II
Contribution of the temperature control to seasonal space heating efficiency		%	2,0
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = - 7 °C (average climate conditions)	Pdh	kW	6,8
Tj = + 2 °C (average climate conditions)	Pdh	kW	4,3
Tj = + 7 °C (average climate conditions)	Pdh	kW	2,8
Tj = + 12 °C (average climate conditions)	Pdh	kW	1,6
Tj = bivalent temperature (average climate conditions)	Pdh	kW	6,8
Tj = operation limit temperature	Pdh	kW	5,4
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	kW	2,8
Bivalent temperature (average climate conditions)	T_{biv}	°C	-7
Bivalent temperature (warmer climate conditions)	T_{biv}	°C	7
Cycling interval capacity for heating (average climate conditions)	Pcych	kW	-

Data at the time of printing. Latest version available on the Internet.

Compress 2000 AWF

CS2000AWF 10 R-S

7738602280

Productdata	Symbol	Unit	7738602280
Degradation coefficient			-
Degradation co-efficient $T_j = -7\text{ °C}$	Cdh		0,9
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T_j /			
$T_j = -7\text{ °C}$ (average climate conditions)	COPd		2,24
$T_j = -7\text{ °C}$ (average climate conditions)	PERd	%	-
$T_j = +2\text{ °C}$ (average climate conditions)	COPd		3,42
$T_j = +2\text{ °C}$ (average climate conditions)	PERd	%	-
$T_j = +7\text{ °C}$ (average climate conditions)	COPd		4,52
$T_j = +7\text{ °C}$ (average climate conditions)	PERd	%	-
$T_j = +12\text{ °C}$ (average climate conditions)	COPd		5,68
$T_j = +12\text{ °C}$ (average climate conditions)	PERd	%	-
T_j = bivalent temperature (average climate conditions)	COPd		2,24
T_j = bivalent temperature	PERd	%	-
T_j = operation limit temperature	COPd		1,83
T_j = operation limit temperature	PERd	%	-
For air-to-water heat pumps: $T_j = -15\text{ °C}$ (if TOL < -20 °C)	COPd		1,22
For air-to-water heat pumps: $T_j = -15\text{ °C}$ (if TOL < -20 °C)	PERd	%	-
For air-to-water heat pumps: Operation limit temperature	TOL	°C	-10
Cycling interval efficiency (average climate conditions)	COP _{cy}		-
Cycling interval efficiency	PER _{cy}	%	-
Heating water operating limit temperature	WTOL	°C	60
Power consumption in modes other than active mode			
Off mode	P _{OFF}	kW	0,014
Thermostat-off mode	P _{TO}	kW	0,024
In standby mode	P _{SB}	kW	0,014
Crankcase heater mode	P _{CK}	kW	0,000
Supplementary heater			
Rated heat output supplementary heater	P _{sup}	kW	2,3
Type of energy input			Electric
Other items			
Capacity control			variable
Emissions of nitrogen oxides (only gas- or oil fired)	NO _x	mg/kWh	-
For air-to-water heat pumps: Rated air flow rate, outdoors		m ³ /h	4030
For brine-to-water heat pumps: Rated brine flow rate, outdoor heat exchanger		m ³ /h	-

Further important information for installation, maintenance as well as recycling and/or disposal are provided within the installation and operating manuals. Read and follow the installation and operating manuals.

Compress 2000 AWF

CS2000AWF 10 R-S

7738602280

System data sheet: To the extent applicable to the product, the following data are based on the requirements of Regulation (EU) 811/2013.

The energy efficiency given in this data sheet for the product combination may deviate from the energy efficiency after its installation in a building, since this is influenced by other factors such as heat loss in the distribution system and the dimensioning of the products in relation to the size and characteristics of the building.

Information about calculating the space heating energy efficiency			
I	Value for the space heating energy efficiency of the preferential space heater	136	%
II	Factor for the weighting of the heat output of the preferential and supplementary heaters of a package system	0,00	-
III	Value of the mathematical expression $294/(11 \cdot \text{Prated})$	3,34	-
IV	Value of the mathematical expression $115/(11 \cdot \text{Prated})$	1,31	-
V	Difference between the seasonal space heating energy efficiency with average and colder climate conditions	20	%
VI	Difference between the seasonal space heating energy efficiency with warmer and average climate conditions	44	%

Seasonal space heating energy efficiency of the heat pump **I** = **1** 136 %

Temperature control (From the data sheet of the temperature control) + **2** 2,0 %

Class: I = 1 %, II = 2 %, III = 1.5 %, IV = 2 %, V = 3 %, VI = 4 %, VII = 3.5 %, VIII = 5 %

Supplementary boiler (From the data sheet of the boiler) (-) - I) x II = - **3** - %

Seasonal space heating energy efficiency (in %)

Solar contribution (III x - + IV x -) x 0,45 x (-) /100) x - = + **4** - %

(From the data sheet of the solar device)

Collector size (in m²)

Storage tank volume (in m³)

Collector efficiency (in %)


Storage tank rating: A⁺ = 0.95, A = 0.91, B = 0.86, C = 0.83, D-G = 0.81

Seasonal space heating energy efficiency of the package system

- with average climate conditions: **5** 138 %

Seasonal space heating energy efficiency class of the package system with average climate conditions

G < 30 %, F ≥ 30 %, E ≥ 34 %, D ≥ 36 %, C ≥ 75 %, B ≥ 82 %, A ≥ 90 %, A⁺ ≥ 98 %, A⁺⁺ ≥ 125 %, A⁺⁺⁺ ≥ 150 %



Seasonal space heating energy efficiency

- with colder climate conditions: **5** 138 - V = 119 %

- with warmer climate conditions: **5** 138 + VI = 184 %